

a) Lieferant supplier's name		Maico Elektroapparate-Fabrik GmbH						
b) Modellkennung (Code) supplier model identifier (code)		WS 320 B (0095.0221)						
c) Spezifischer Energieverbrauch specific energy consumption SEC class - climate zone „average“		SEC	kalt / cold	mittel / average		warm / warm		kWh /(m²·a)
			-82,16	-42,5		-17,2		
				A+				
d) Typ typology			RVU	x	BVU	x		
			NRVU	—	UVU	—		
e) Art des eingebauten / einzubauenden Antriebes type of drive installed / intended to be installed			multi-speed	—	installed	x		
			VSD	x	intended to be instal.	—		
f) Art des Wärmerückgewinnungssystems (WRG) type of heat recovery system			rekuperativ / recuperative	x	regenerativ / regenerative	—	keines / none	
g) Temperaturänderungsgrad der WRG thermal efficiency of heat recovery		η _t	92,8				%	
h) Höchster Luftvolumenstrom maximum flow rate			300				m³/h	
i) Elektrische Eingangsleistung Ventilatorantrieb electric power input of the fan drive			79,6				W	
j) Schallleistungspegel sound power level		L _{WA}	44				dB[A]	
k) Bezugs-Luftvolumenstrom reference flow rate			0,0583				m³/s	
l) Bezugsdruckdifferenz reference pressure difference			50				Pa	
m) Spezifische Eingangsleistung specific power input		SPI	0,18				W/(m³/h)	
n) Steuerungsfaktor und Steuerungstypologie control factor and control typology			CTRL	MISC		X-Value		
			0,85	1,1		2		
o) Innere Höchstlecklufrate / Äußere Höchstlecklufrate max. internal leakage rate / max. external leakage rate			innere / internal	2	äußere / external	2	%	
p) Mischrate mixing rate			—				%	
q) Lage und Beschreibung optische Filterwarnanzeige position and description of visual filter warning			LED - replace the filter continuously to preserve the device properties					
r) Anweisungen für Anbringung regelbarer AUL- / ABL-Gitter instructions to install regulated supply/exhaust grilles			—					
s) Internetadresse für Anweisungen zur Zerlegung/Demontage internet address for disassembly instructions			www.maico-ventilatoren.com					
t) Druckschwankungsempfindlichkeit Luftstrom airflow sensitivity to pressure variations at -20 Pa / +20 Pa			—				%	
u) Luftdichtheit zwischen innen und außen indoor / outdoor air tightness			—				m³/h	
v) Jährlicher Stromverbrauch annual electricity consumption		AEC	2,1				kWh/(m²·a)	
w) Jährliche Einsparung an Heizenergie annual heating saved		AHS	kalt/cold	mittel / average	warm / warm		kWh/(m²·a)	
			92,1	47,1	21,3			